



zazen Raindrop Shower Filter (ZAZ505)

INSTALLATION AND USER INSTRUCTIONS

Congratulations! You have just purchased one of the finest shower filters in the world! The exclusive zazen Raindrop Shower Filter has been designed to complement any bathroom.



Your zazen Raindrop Shower Filter features:

- ✓ Large 15.24cm (6") head with 60 chrome nozzles
- ✓ 25cm (10") Hi/Lo shower arm allows for a 50cm (20") height and angle range ... adjust the height to suit
- ✓ 38,000 litre Rated Capacity ... 12 months
- ✓ Reduces Chlorine ... enjoy a healthier showering experience
- ✓ Reduces odours and improves water clarity
- ✓ Reduces Radon, Rust, Scale, Sediment & Heavy Metals including Copper
- ✓ Prohibits growth of Bacteria, Fungi and Algae within the filter itself
- ✓ Easy to Install (5 minutes) and also replace the shower filter cartridge... no plumber required

FILTER CARTRIDGE LIFE	OPERATING SPECIFICATIONS
<ul style="list-style-type: none"> ● 12 months / 38,000 litres ● Replacement zazen Filter Cartridge (Part 507) <p>WARNING – the filter cartridge must be replaced at least once per year. Failure to replace may result in deterioration and instability of the showerhead.</p> <p>* Continued use after 2 years may cause damage to your shower head.</p> <p>Note: The Filter Cartridge life may be influenced by the quality of your source water.</p>	<ul style="list-style-type: none"> ● Rated Service Flow: 9 litres/min ● WELS Rating: 3 ● Rated Capacity: 38,000 litres (12 months) ● Operating Pressure: 20 – 110 psi (KPA 200 – 700) ● Operating temperature: 4 – 48.9° C (40 – 120° F) ● Connects to standard Australian Pipe 20mm (inside 15mm) <p>Standards: AS/NZS3662 WELS Registration: S11808</p>

* BACK FLUSH INSTRUCTIONS: In areas where there is a high level of water sediment, to improve water flow, open your showerhead and remove the filter cartridge (follow the directions for the filter replacement Step 1). Turn the filter cartridge 180° and reinsert into the showerhead in the opposite direction from which it was previously positioned. Replace the showerhead faceplate – and turn on the water until it runs clear from built up sediment that may be clogging the filter screens.

- The filter cartridge is reversible and can be used in either direction.
- The media in the cartridge is still usable for the original 38,000 litres or 1 year maximum.

REGISTER YOUR PRODUCT ONLINE (If you did not purchase from zazen Water directly). zazen will automatically remind you when you need to replace your filter cartridge in 12 months.

LIMITED WARRANTY: zazen Water warrants to the owner of this product, for a period of 90 days from the date of purchase, that it is free from defects in material and workmanship and agrees that it will, at its option, either repair the defect or replace the defective product or part thereof at no charge to the purchaser for parts and labor.

If within 90 days from the date of purchase the product proves to be defective for any reason, return it post paid to zazen Water at the address below for repair or replacement at no charge, thank you.

This warranty does not of course apply to any product where the exterior of which has been damaged or defaced, which has been subjected to commercial usage, misuse, abnormal service or handling or which has been altered or modified in design or construction.

Enjoy your healthier showering experience and thank you for your valued support and custom.

The WaterMark Certification applies to the products performance as a shower for personal bathing and has not assessed the products ability to reduce contaminants' in the water supply.



helping you live a longer, healthier life
... the zazen Water team

1300 78 24 25 www.zazen.com.au




POSTAL: PO Box 219, Red Hill QLD 4059
OR U7/38 Bishop Street, Kelvin Grove QLD 4059, Australia



INSTALLATION INSTRUCTIONS

PLEASE READ THE FOLLOWING INSTALLATION PRECAUTIONS AND INSTRUCTIONS CAREFULLY AND COMPLETELY, thank you.

ITEMS INCLUDED – you will also need a Phillips Head screwdriver

			
Chrome Shower Head – includes Black Seal inside shower head and black washer inside Inlet Nut	Stainless Steel Hi/Low Arm – includes black washer inside the Inlet Nut	Filter Cartridge (Part # 507) Remove Stickers from top and bottom	Teflon Tape + 6 Screws for the Chrome Shower Head

IMPORTANT: Please ensure that the 2 black washers (which are already installed into the inlet nut and the shower head) are in place and have NOT dropped out when you unpacked and moved the shower filter. Your shower filter has been checked and packed with these washers in place as described.

INSTALLING THE ZAZEN RAINDROP SHOWER FILTER

STEP 1 Unscrew the 6 screws from the shower head and insert the filter cartridge inside the shower head.

- The filter cartridge inserts easily – just push (before you insert the new cartridge, remove stickers from top and bottom).
- Ensure you leave the Black Seal (already inserted into the shower head as shown) in place.



STEP 2 Secure front and back of showerhead together with the 6 screws.

- There are 6 screw holes evenly spaced around the outside of the showerhead.
- Front piece of showerhead will click into place against the back piece of showerhead.
- When you feel this lock, the screw holes are perfectly aligned.



STEP 3 Remove your existing showerhead from the shower pipe and wrap the end of the pipe with Teflon tape (included).

- The tape helps to seal the connection tightly so water does not leak from wall connection.



STEP 4 Attach Hi/Lo arm to your shower pipe by turning the entire arm until the Inlet Nut is secure and the Hi/Lo arm is straight.

- Ensure the black washer provided is still inside the Inlet Nut before you screw onto the shower pipe.



STEP 5 Attach the showerhead to the Outlet Nut on the Hi/Lo arm and position Swivel Joints at desired angles and secure Wing Nuts tightly in place.

Run the shower to rinse the filter cartridge and until the water runs clear. Your new Shower Filter is ready to use...



INSTALLATION CARE – FLOW CONTROLLER: Care should be exercised during installation to ensure that the male connecting threads do not damage the flow controller.

Congratulations! We know you will love your healthier shower experience... thank you for your valued custom and support. With appreciation, the zazen Water team

